



## 7-in AC/DC PORTABLE MONITOR (HDMI, COMPOSITE)

# S-1071C+



### Introduction:

S-1071C+ is a HDMI monitor, offering HDMI input with Peaking focus assist, HDMI audio meter display, false color, zebra stripes, Canon DSLR scale zoom-in, and front & rear dual TALLY light, video flip, customer editable video title, and safety mark display.

S-1071C+ accepts 1 HDMI, 1 Composite video, 1 stereo audio input, and has 1 Composite video loop through output.

It's powered via a 4-pin XLR 6.5-17V DC connector or V-mount / Gold-mount / Snap-on DV battery mounts.

### Features:

- ◆ 1024×RGB×600
- ◆ 16:9 / 4:3 adjustable
- ◆ HDMI, Composite video, Stereo audio inputs
- ◆ Peaking focus assist (HDMI)
- ◆ 2-ch audio meter display (HDMI)
- ◆ False color filter (HDMI)
- ◆ Zebra stripes (HDMI)
- ◆ Dual 3-color TALLY light
- ◆ Underscan / Overscan switch
- ◆ Canon DSLR scale zoom-in
- ◆ Video flip
- ◆ Customer editable video TITLE
- ◆ V-mount / Gold mount option
- ◆ Snap-on DV mounts option

### Specifications:

#### LCD Performance

Size	7.0 inches
Resolution	1024×RGB×600
Aspect ratio	16:9/4:3
Color system	NTSC/PAL
Brightness	400cd/m2
Contrast	900:1
Color	16.77 million colors
Viewing angle	H/V:160/160

#### Input and Output

Input	1 BNC	1 Composite in
	1 HDMI	1 HDMI in
	2 RCA	Stereo audio (L, R) in
Output	1 BNC	1 Composite loop through out
	1 HDMI	1 HDMI loop through out

#### Video Format

HDMI	480i / 576i / 480P / 576P
	1080i (60 / 59.94 / 50)
	720p (60 / 59.94 / 50)
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)
Composite	PAL/NTSC

#### General


Working voltage	DC/Battery 6.5V-17V
Power consumption	≤9W
Working temperature	0 C ~ +40 C
Working humidity	10% ~ 90%
Storage temperature	-15 C ~ +60 C
Storage humidity	10% ~ 90%
Dimensions	192×139×47mm
Net weight	550g

### Simple Package includes:



Cold shoe / Screw Head   Sun Hood   Battery mount   LCD Protector   4-pin XLR AC-DC adapter

### Luxury Package has additional:



S-7107 HDMI cable with mini HDMI adaptor   S-7101 D-tap to 4-pin XLR cable   Pan-tilt arm trestle (screw mount)   Carrying case

### SWIT Electronics Co., Ltd.

Website: [www.swit.cc](http://www.swit.cc)

Email: [contact@swit.cc](mailto:contact@swit.cc)

Tel: +86 25 85805753

Fax: +86 25 85805296

### Distributed by:

