

S-3822A/S

2-ch Simultaneous Battery Charger & Adaptor



S-3822A
for Gold Mount



S-3822S
for V-Mount

Features

- ◆ Portable battery charger
- ◆ 2-ch simultaneous charging
- ◆ 3A charging current per channel
- ◆ LED charging indicators
- ◆ Support AC to 4-pin XLR output

Specifications:

Input	100~240VA, 50/60Hz
Power	136W(Max)
Charging Output	DC 16.8V, 3A(Max)×2
Adapting Output	DC 15V, 6A(Max)
Working Temperature	0°C ~ +40°C
Working Humidity	10%~90%
Dimension	228mm×140mm×86mm(S-3822A) 228mm×140mm×120mm(S-3822S)
Weight	Appx 1.0kg



Can charge 2x **V-mount / Gold mount** batteries simultaneously. The charging output is DC **16.8V, 3Ax2**



LED indicates the charging status for each channel:
Red: on charging, < 80%;
Yellow: on charging, ≥80%;
Green: charging finished.



AC-DC adapting output via 4-pin XLR female connector. Offer DC **15V, 6A, 90W** output. (will not output when battery is charging)

SWIT Electronics Co., Ltd.

Website: www.swit.cc

Email: contact@swit.cc

Tel: +86 2585805753

Fax: +86 2585805296

Distributed by: