SWIT®



Introduction:

The S-2041 on-camera LED light adopts the new generation Chip-on-board LED, which integrates the LEDs into a chip with high brightness output but in smaller size, and the most remarkable, it offers a equally spread, soft, glareless light, similar to the traditional Halogen bulb light.

COB LED On-camera Light S-2041

Features:

- Chip on board COB LED technology
- > 23W, 1800Lux @ 1 meter, dimmerable
- > 100W equivalent output
- > Single shadow, glareless
- > 60° wide beam angle, equally spread
- › Cool touch
- > 5000K color temperature
- > 5600K and 3200K filter
- > 6-17V wide input voltage
- > Interchangeable DV mount and battery
- > Screw and cold shoe mount



1 By standard DV batteries (via S-7004 quick interchangeable DV plate)

| | N | | |
|--|---|---------|-------------------|
| | | S-7004F | SONY NP-970 |
| | | S-7004U | SONY BP-U60 |
| | | S-7004D | Panasonic D54S |
| | | S-7004B | Panasonic VW-VBG6 |
| | | S-7004C | Canon BP-945 |
| | | S-7004E | Canon DSLR LP-E6 |
| | | S-7004I | JVC SSL-JVC50 |
| | | S-7004V | JVC BN-VF823 |

2 By D-tap DC power cable



14.4V D-tap power input

Specifications:

| Input voltage | DC 6V-17V |
|-----------------------|--|
| Power consumption | 23W |
| Equivalent | 100W |
| Beam angle | Approx. 60° |
| Color temperature | 5000K and 5600K/3200K switchable |
| Color rendering index | 85 |
| Illuminance | 1800Lx @ 1m distance and 1m diameter scale |
| Power connector | D-tap cable, DV mount connection |
| Weight | 400g |
| Dimension | 103×157×84mm |

SWIT Electronics Co., Ltd.

Website: www.swit.cc Email: contact@swit.cc

Tel: +86 25 85805753 Fax: +86 25 85805296

Advantages of COB LED

Traditional




Integrate traditional LED array into a chip



Wider beam angle, equally spread, no visible edge







Single shadow